


# EMBOUT "S" : JIC 74°

## FJ



NORMES : ISO 8434-2  
SAE J516/J514

FILETAGE : UNF  
ASME B1.1



Notes

D.N.		Référence		Filetage	Dimensions (mm)			
mm	"	Code	Désignation	F	C	Ø inter.	L	A
6	1/4"	1500611	S06 FJ 7/16	7/16"-20	15	4,0	43,0	15,0
6	1/4"	1500613	S06 FJ 1/2	1/2"-20	17	4,0	45,0	14,5
6	1/4"	1500614	S06 FJ 9/16	9/16"-18	19	4,0	45,0	15,9
8	5/16"	◆	S08 FJ 7/16	7/16"-20	15	5,5	45,0	16,5
8	5/16"	1500813	S08 FJ 1/2	1/2"-20	17	5,5	45,0	16,5
8	5/16"	1500814	S08 FJ 9/16	9/16"-18	19	5,5	45,0	15,9
8	5/16"	◆	S08 FJ 3/4	3/4"-16	24	5,5	47,5	19,0
10	3/8"	1501014	S10 FJ 9/16	9/16"-18	19	7,0	47,0	16,0
10	3/8"	1501019	S10 FJ 3/4	3/4"-16	24	7,0	48,5	16,1
10	3/8"	◆	S10 FJ 7/8	7/8"-14	27	7,0	53,0	18,2
12	1/2"	1501219	S12 FJ 3/4	3/4"-16	24	9,5	53,0	16,7
12	1/2"	1501222	S12 FJ 7/8	7/8"-14	27	9,5	54,5	18,8
12	1/2"	◆	S12 FJ 1"1/16	1"1/16-12	32	9,5	56,0	23,0
16	5/8"	1501622	S16 FJ 7/8	7/8"-14	27	12,0	57,5	18,8
16	5/8"	1501627	S16 FJ 1"1/16	1"1/16-12	32	12,0	59,0	21,6
20	3/4"	1502027	S20 FJ 1"1/6	1"1/16-12	32	14,5	65,0	22,6
20	3/4"	1502030	S20 FJ 1"3/16	1"3/16-12	36	14,5	65,5	22,1
20	3/4"	◆	S20 FJ 1"5/16	1"5/16-12	41	14,5	66,0	24,3
25	1"	◆	S20 FJ 1"3/16	1"3/16-12	36	21,0	80,5	25,5
25	1"	1502533	S25 FJ 1"5/16	1"5/16-12	41	21,0	81,0	24,8
25	1"	◆	S25 FJ 1"5/8	1"5/8-12	50	21,0	82,5	27,5
32	1"1/4	1503241	S32 FJ 1"5/8	1"5/8-12	50	26,5	89,0	28,0
32	1"1/4	◆	S32 FJ 1"7/8	1"7/8-12	55	26,5	91,5	30,5
40	1"1/2	1504048	S40 FJ 1"7/8	1"7/8-12	55	32,0	102,0	31,5
40	1"1/2	◆	S40 FJ 2"1/2	2"1/2-12	70	32,0	104,0	33,5
50	2"	1505064	S50 FJ 2"1/2	2"1/2-12	70	44,0	109,5	33,5

