


EMBOUT "S" : JIC 74°

F9J

coudé à 90°

NORMES : ISO 8434-2
SAE J516/J514

FILETAGE : UNF
ASME B1.1



Notes

D.N.		Référence		Filetage	Dimensions (mm)				
mm	"	Code	Désignation	F	C	Ø inter.	L	A	B
6	1/4"	1520611	S06 F9J 7/16	7/16"-20	15	4,0	52,0	23,0	27,0
6	1/4"	1520613	S06 F9J 1/2	1/2"-20	17	4,0	52,0	23,0	26,0
6	1/4"	1520614	S06 F9J 9/16	9/16"-18	19	4,0	52,0	23,0	29,0
8	5/16"	1520813	S08 F9J 1/2	1/2"-20	17	5,5	59,0	30,0	29,0
8	5/16"	1520814	S08 F9J 9/16	9/16"-18	19	5,5	59,0	33,0	30,0
8	5/16"	◆	S08 F9J 3/4	3/4"-16	24	5,5	59,0	31,0	34,0
10	3/8"	1521014	S10 F9J 9/16	9/16"-18	19	7,0	59,0	35,0	33,0
10	3/8"	1521019	S10 F9J 3/4	3/4"-16	24	7,0	64,0	35,0	34,0
10	3/8"	1521022	S10 F9J 7/8	7/8"-14	27	7,0	64,0	35,0	37,0
12	1/2"	1521219	S12 F9J 3/4	3/4"-16	24	9,5	74,0	39,0	39,0
12	1/2"	1521222	S12 F9J 7/8	7/8"-14	27	9,5	74,0	39,0	41,0
12	1/2"	◆	S12 F9J 1"1/16	1"1/16-12	32	9,5	74,0	41,0	48,0
16	5/8"	1521622	S16 F9J 7/8	7/8"-14	27	12,0	85,0	48,0	45,0
16	5/8"	1521627	S16 F9J 1"1/16	1"1/16-12	32	12,0	85,0	48,0	51,0
20	3/4"	◆	S20 F9J 7/8	7/8"-14	27	14,5	99,0	58,0	56,0
20	3/4"	1522027	S20 F9J 1"1/16	1"1/16-12	32	14,5	99,0	50,0	51,0
20	3/4"	◆	S20 F9J 1"3/16	1"3/16-12	36	14,5	99,0	58,0	54,0
20	3/4"	1522033	S20 F9J 1"5/16	1"5/16-12	41	14,5	99,0	50,0	55,0
25	1"	◆	S25 F9J 1"1/16	1"1/16-12	32	21,0	129,0	74,0	69,0
25	1"	1522533	S25 F9J 1"5/16	1"5/16-12	41	21,0	129,0	72,0	67,0
25	1"	◆	S25 F9J 1"5/8	1"5/8-12	50	21,0	129,0	74,0	77,0
32	1"1/4	1523241	S32 F9J 1"5/8	1"5/8-12	50	26,5	153,0	92,0	87,0
32	1"1/4	◆	S32 F9J 1"7/8	1"7/8-12	55	26,5	153,0	92,0	91,0
40	1"1/2	1524048	S40 F9J 1"7/8	1"7/8-12	55	32,0	179,0	108,0	100,0
50	2"	1525064	S50 F9J 2"1/2	2"1/2-12	70	44,0	218,0	142,0	126,0