


EMBOUT "S" : BSP 60°

FB


**NORMES : BS 5200/86
(NCB174)**

**FILETAGE : BSPP
ISO 228**



Notes
Version Oring, nous consulter

D.N.		Référence		Filetage	Dimensions (mm)			
mm	"	Code	Désignation	F	C	Ø inter.	L	A
6	1/4"	1400610	S06 FB 1/8	1/8" -28	14	4,0	42,0	15,9
6	1/4"	1400613	S06 FB 1/4	1/4" -19	19	4,0	44,0	17,6
6	1/4"	1400617	S06 FB 3/8	3/8" -19	22	4,0	45,0	18,7
8	5/16"	1400813	S08 FB 1/4	1/4" -19	19	5,5	44,0	17,6
8	5/16"	1400817	S08 FB 3/8	3/8" -19	22	5,5	45,0	18,7
8	5/16"	1400821	S08 FB 1/2	1/2" -14	27	5,5	47,0	20,5
10	3/8"	1401013	S10 FB 1/4	1/4" -19	19	7,0	48,0	17,7
10	3/8"	1401017	S10 FB 3/8	3/8" -19	22	7,0	49,0	18,8
10	3/8"	1401021	S10 FB 1/2	1/2" -14	27	7,0	51,0	20,6
12	1/2"	1401221	S12 FB 1/2	1/2" -14	27	9,5	53,0	21,2
12	1/2"	1401223	S12 FB 5/8	5/8" -14	30	9,5	51,0	18,8
12	1/2"	1401227	S12 FB 3/4	3/4" -14	32	9,5	57,0	25,3
16	5/8"	1401621	S16 FB 1/2	1/2" -14	27	12,0	61,0	21,2
16	5/8"	1401623	S16 FB 5/8	5/8" -14	30	12,0	61,0	21,3
16	5/8"	1401627	S16 FB 3/4	3/4" -14	32	12,0	63,0	22,8
20	3/4"	1402027	S20 FB 3/4	3/4" -14	32	14,5	67,0	22,8
20	3/4"	1402034	S20 FB 1"	1" -11	38	14,5	69,0	24,5
25	1"	1402534	S25 FB 1"	1" -11	38	21,0	79,0	25,0
32	1"1/4	1403242	S32 FB 1"1/4	1"1/4 -11	50	26,5	92,5	34,5
40	1"1/2	1404049	S40 FB 1"1/2	1"1/2 -11	55	32,0	99,0	35,0
50	2"	1405060	S50 FB 2"	2" -11	70	44,0	112,5	40,5

